



MODEL MTO2V 10040

Proper to contemporarily cut both in horizontal sense that vertical with a speed of cut from $0 \div 25$ m/min.

Slide on binary type U 80 / (a richieta) ROTAIA S10

Total power Kw 73,5

Depth of Vertical max420mm.

Depth of Horizontal cut max250mm

Vertical disk f1200mm.

Horizontal disk f 700mm.

Recommended generator KVA125

ELECTRIC MOTORS

· Vertical cut kw 37

Type IP 55 Class F n 0, 87÷ 0,92V 380 50 Hz B3

Horizontal cut Kw30

Type IP 55 Class F ŋ 0, 87÷ 0,92V 38050 Hz B3

Advancement Kw4

Type IP 55 Class F ŋ 0, 80÷ 0,92V 380 50 Hz B5

• I install hydraulic Kw 2.2

Type IP 55 Class F n 0, 80÷ 0,92V 380 50 Hz B5

With commands of driving to low tension as foreseen by the law Opportunely proportionate and pulsating of march / single arrest for every motor.

SAFFTY

The machine is provided of electric devices of block that make her/it sure and of acoustic and bright device that warns that the cars it is in movement. And' provided of protections on all the mechanical organs in movement and protection on the disks up to maximally possible.

I INSTALL HYDRAULIC

Pomp to gears. distributor to 3 elements Brought 10 litri/1' Pressure 100 ÷ 150 bar Ability reservoir 50Lt.

ADVANCEMENT OF CUT

Hydraulic to varying course independent operated through lever inversion of march with point of madman speed max. 50 @m/min. 4 to empty 4 wheels engines



LOOM

It structures in steel on purpose studied for a' tall resistance, elettrosaldato. Articulation vertical cut, to hydraulic command through hydraulic martinetto to double effect; Translation cart for Horizontal loom through martinetto to double effect And it flows on pads and adjustable guides to annul the game of usury. Driving Horizontal cut through hydraulic martinetto to double effect integrated in a system of levers.

MEASURE AND MASS

Width	_2000	mm. ~
Lenght	2600	mm. ~
Height_	1800	mm. ~
Weigth	280	n Ka ~

Gives technical and characteristics can suffer variations