



# **MODEL MTO2V 18040**

Proper to contemporarily cut both in horizontal sense that vertical with a speed of cut from 0 ÷ 25 m/min. Unlike the model MTOV the vertical cut is predisposed to the left for the assemblage of the disk. Solution that allows to use the machine for the only Vertical tracings (in case of lack of the model MTV.) Slide on binary type ROTAIA S14 Total power Kw 130,5 Depth of Vertical max 420 mm. Depth of Horizontal cut max 250mm Vertical disk f 1200mm. Horizontal disk f 700mm. Recommended generator KVA 225

# **ELECTRIC MOTORS**

- Vertical cut kw 75 Type IP 55 Class F ŋ 0, 87÷ 0,92V 380 50 Hz B3
- Horizontal cut Kw 45 Type IP 55 Class F n 0, 87÷ 0,92V 38050 Hz B3
- Advancement Kw7,5 Type IP 55 Class F n 0, 80÷ 0,92V 380 50 Hz B5 I install hydraulic Kw 3
  - Type IP 55 Class F n 0, 80÷ 0,92V 380 50 Hz B5

With commands of driving to low tension as foreseen by the law Opportunely proportionate and pulsating of march / single arrest for every motor.

### SAFETY

The machine is provided of electric devices of block that make her/it sure and of acoustic and bright device that warns that the cars it is in movement. And' provided of protections on all the mechanical organs in movement and protection on the disks up to maximally possible.

### **I INSTALL HYDRAULIC**

Pomp to gears. distributor to3 elements Brought 10 litri/1' Pressure 100 ÷ 150 bar Ability reservoir 50Lt.

### **ADVANCEMENT OF CUT**

Hydraulic to varying course independent operated through lever inversion of march with point of madman speed max. 50 @m/min. 4 to empty 4 wheels engines

# **SINCE 1968**

### LOOM

It structures in steel on purpose studied for a' tall resistance, elettrosaldato. Articulation vertical cut, to hydraulic command through hydraulic martinetto to double effect; Translation cart for Horizontal loom through martinetto to double effect And it flows on pads and adjustable guides to annul the game of usury. Driving Horizontal cut through hydraulic martinetto to double effect integrated in a system of levers.

## **Measure and Mass**

| Width   | 2250 | mm. ~ |
|---------|------|-------|
| Lenght_ | 4500 | mm. ~ |
| Height_ | 1900 | mm. ~ |
| Weigth_ | 5300 | Kg. ~ |

Gives technical and characteristics can suffer variations



40 ANNI DI ESPERIENZA NEL SETTORE DELLE MACCHINE CAVATUFO E CAVAPIETRA Magisa ® - Macchine Cavatufo e Cavapietra - 72017 - Ostuni (BR) Italy - Zona industriale

> tel. 0039 / 0831 304559 - fax. 0039 - 0831 330294 www.magisa.it - info@magisa.it

Partita iva 02044780746